


PERUGINO

sporgenza max | **max projection** | maximale Ausladung
avancée maximale | salida máx | saliência máxima

300 cm



ONLY ON REQUEST

non a stock, solo su richiesta
not in stock, only on request
Nicht auf Lager, nur auf Anfrage

pas en stock, uniquement sur demande
no en stock, solo bajo pedido
não em estoque, apenas a pedido



Battesimo di Cristo, disegno
il Perugino - 1448 - 1523 circa



PERUGINO

euroflex A TOUCH OF SHADE

Tenda a bracci su staffe indipendenti con supporto braccio laterale fisso. Dimensioni massime: larghezza 600 cm e sporgenza 300 cm.

Folding arm awning on independent brackets with fixed lateral arm supports. Maximum dimensions: 600 cm width and 300 cm projection.

Gelenkarm-Markise auf unabhängige laterale feste Armträger. Maximalgröße: Breite 600 cm; Ausladung 300 cm.

Store à bras sur étriers indépendants avec support bras latéral fixe. Dimensions maximales: largeur 600 cm et avancée 300 cm.

Toldos con brazos sobre soportes independientes, soporte brazo lateral fijo. Dimensiones máximas: ancho 600 cm y salida 300 cm.

Toldo com braços sobre estribos independentes com suporte braço lateral fixo. Dimensões máximas: largura 600 cm e saliência 300 cm.



arm support



arm support



heavy lux terminal bar



PVC heavy terminal bar cap

AWNING MINIMUM WIDTH

sporgenza braccio
arm projection
Arm Ausladung
avancée du bras
salida brazo
saliência braço

larghezza tenda minima » 1 coppia bracci
awning minimum width » 1 pair of arms
Mindestbreite » 1 Paar von Armen
largeur minimum store » 1 paire de bras
ancho mínimo toldo » 1 par de brazos
largura mínima de toldo com um par de braços

150
175
200
225
250
275
300

190 cm
214 cm
238 cm
262 cm
290 cm
314 cm
338 cm

WIND RESISTANCE CLASS ACCORDING TO THE EUROPEAN STANDARD UNI EN 13561

Classe di resistenza al vento secondo la normativa europea UNI EN 13561
Wind resistance class according to the European standard UNI EN 13561
Windwiderstandsklasse nach der Europäischen Norm EN 13561

Classe de résistance au vent conformément à la réglementation européenne UNI EN 13561
Clase de resistencia al viento según la Normativa Europea UNI EN 13561
Clase de resistência ao vento de acordo com as normas europeias UNI EN 13561

larghezza
width
Breite
largeur
ancho
largura

sporgenza tenda aperta
open awning projection
Ausladung geöffnete Markise
avancée store ouvert
salida toldo abierto
saliência toldo aberto

classe
class
Klasse
classe
clase
classe

tubo avvolgitore
roller tube
Tuchwelle
tube enrouleur
tubo de enrollle
tubo enrolador


600 cm
600 cm

300 cm
275 cm

1
2

Ø 78 mm
Ø 78 mm

ARM LENGTH AND INCLINATION



CONTINUOUS ADJUSTMENT

0° - 78°

regolazione continua
cambiando la posizione del disco
continuous adjustment
changing disk's position
Kontinuierliche Einstellung
wobei die Position der Scheibe geändert wird
réglage en continue
en changeant la position du disque
ajuste continuo
de mudando a posição do disco
ajuste continuo
cambiando la posición del disco

MAIN ARM

STAR PLUS

SP. MAX


350 cm

OPTIONAL ARM


SP. MAX

GALAXY PLUS	350 cm
ARIES PLUS	350 cm
STAR PLUS	350 cm
STAR	350 cm
ARIES	350 cm
PEGASUS PLUS	350 cm
PEGASUS	350 cm
CASSIOPEA	350 cm
CASSIOPEA LED	350 cm

WALL/CEILING BRACKET



AWNING SIZES



HOOD



ROLLÒ



LED SYSTEM

